PYRAMEX

LATEX DIPPED

LATEX | ABRASION | CONTACT HEAT | PUNCTURE | TEAR

GL503

Polyester | Latex | Crinkle

ANSI/ISEA 105 A1 (4, 3)

EN388 3242X

EN407 X2XXXX

CE UKCA

ANSI/ISEA 105 – CUT A1 | ABRASION 4 | PUNCTURE 3
EN388 – ABRASION 3 | CUT 2 | TEAR 4 | PUNCTURE 2 | CUT TDM-100 X
EN407 – CONTACT HEAT 2

Durable crinkle latex coating on the palm and fingers offers superior contact on dry or wet surfaces by channeling liquids away // 10 gauge polyester liner offers a balance between comfort, durability, and moisture resistance // Contact heat protection up to 482°F/250°C // Packaging option for vending machines available



Suggested Applications

Assembly // Bottling and Canning // Manufacturing // Recycling and Sanitation

Glove Breakdown

Type: Dipped Glove
Material: Crinkle Latex
Outer Liner: 10 Gauge Polyester
Cuff: Polyester + Latex Elastic

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Glove Sizing

GL503 S – 2XL | GL503VP XL

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Packaging

	Inner Polybag	Outer Polybag	Case
GL503	–	12 Pair	120 Pair
GL503VP	1 Pair Rolled	12 Pair	120 Pair
Made in China			

Product markings may vary // Updated as of 03.26

PYRAMEX

LATEX DIPPED

LATEX | ABRASION | CONTACT HEAT | PUNCTURE | TEAR

GL503

Polyester | Latex | Crinkle

ANSI/ISEA 105 A1 4 3 | EN388 3242X | EN407 X2XXXX | CE | UKCA

ANSI/ISEA 105 – CUT A1 | ABRASION 4 | PUNCTURE 3
EN388 – ABRASION 3 | CUT 2 | TEAR 4 | PUNCTURE 2 | CUT TDM-100 X
EN407 – CONTACT HEAT 2

Durable crinkle latex coating on the palm and fingers offers superior contact on dry or wet surfaces by channeling liquids away // 10 gauge polyester liner offers a balance between comfort, durability, and moisture resistance // Contact heat protection up to 482°F/250°C // Packaging option for vending machines available



Suggested Applications

Assembly // Bottling and Canning // Manufacturing // Recycling and Sanitation

Glove Breakdown

Type: Dipped Glove
Material: Crinkle Latex
Outer Liner: 10 Gauge Polyester
Cuff: Polyester + Latex Elastic

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov
This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Packaging

	Inner Polybag	Outer Polybag	Case
GL503	–	12 Pair	120 Pair
GL503VP	1 Pair Rolled	12 Pair	120 Pair
Made in China			

Product markings may vary // Updated as of 03.26

Glove Sizing

GL503 S – 2XL | GL503VP XL

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.