PYRAMEX

INSULATED LATEX DIPPED

LATEX | ABRASION | CUT | HIGH VISIBILITY | INSULATED | PUNCTURE | TEAR

GL504

Acrylic | Latex | Sandy

ANSI/ISEA 105 A2 (3, 2)
EN388 2232X
EN511 X2X
CE UKCA

ANSI/ISEA 105 – CUT A2 | ABRASION 3 | PUNCTURE 2
EN388 – ABRASION 2 | CUT 2 | TEAR 3 | PUNCTURE 2| CUT TDM-100 X
EN511 – CONTACT COLD 2

Sandy latex coating on the palm and fingers provides an effective grip in dry and oily situations // 10 gauge acrylic liner delivers insulation, moisture resistance, comfort, and durability // High-visibility for easy recognition // Contact cold protection down to as low as 14°F/-10°C // Knit cuff creates a snug fit to keep out debris

Suggested Applications

Commercial Fishing // Construction //
Food Processing // Outdoor Activities //
Refrigerated Area // Utilities

Glove Breakdown

Type: Insulated Dipped Glove
Material: Sandy Latex
Outer Liner: 10 Gauge Acrylic
Cuff: Acrylic + Latex Elastic

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Product markings may vary // Updated as of 10.25



Packaging

	Outer Polybag	Case	Made in China
GL504	12 Pair	120 Pair	

Glove Sizing

GL504 S – 2XL

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.