PYRAMEX

INSULATED NITRILE DIPPED

NITRILE | ABRASION | CUT | PUNCTURE | TEAR | HIGH VISIBILITY | INSULATED | IMPACT

GL612C

HPPE + Acrylic | Nitrile| Sandy | TPR

ANSI/ISEA 105 A6 (6 4) | ANSI / ISEA 138 2 | EN388 4X43EP | EN511 X2X | CE | UKCA

ANSI/ISEA 105 – CUT A6 | ABRASION 6 | PUNCTURE 4
ANSI/ISEA 138 – IMPACT 2
EN388 – ABRASION 4 | CUT X | TEAR 4 | PUNCTURE 3 | CUT TDM-100 E | IMPACT P
EN511 – CONTACT COLD 2



Sandy nitrile coating on the palm and fingers provides an effective grip in dry and oily situations // 13 gauge outer HPPE cut-resistant liner provides comfort and dexterity // 10 gauge inner acrylic liner delivers insulation and moisture resistance // Contact cold protection down to as low as 14°F/-10°C // Custom-designed impact protection shields back of hand // Reinforced thumb reduces stress in high-wear area // High-visibility liner for easy recognition // Knit cuff creates a snug fit to keep out debris

Suggested Applications

Construction // Masonry // Material Handling // Petrochemical Industries

Glove Breakdown

Type: Insulated Dipped Glove
Material: Sandy Nitrile
Outer Liner: 13 Gauge HPPE
Inner Liner: 10 Gauge Acrylic
Cuff: HPPE + Acrylic + Latex Elastic
Impact: Thermoplastic Rubber

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Updated as of 10.25

Packaging

	Inner Polybag	Outer Polybag	Case	
GL612C	1 Pair	6 Pair	60 Pair	Made in China

Glove Sizing

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.