PYRAMEX

NITRILE DIPPED

NITRILE | ABRASION | PUNCTURE | TEAR

GL615

Nylon + Spandex | Nitrile | Micro-Foam

ANSI/ISEA 105 A1 6 2

EN388 4131X

CE UKCA

ANSI/ISEA 105 – CUT A1 | ABRASION 6 | PUNCTURE 2
EN388 – ABRASION 4 | CUT 1 | TEAR 3 | PUNCTURE 1 | CUT TDM-100 X

Micro-foam nitrile coating on palm and fingers offers an excellent grip on dry or wet surfaces by channeling liquids away // 15 gauge nylon/spandex liner is comfortable and breathable // Glove design offers distinctive touch sensitivity // Knit cuff creates a snug fit to keep out debris // Dark liner and coating hide stains



Suggested Applications

Automotive // Construction // General Duty/Purpose // Horticulture // Manufacturing // Warehousing

Glove Breakdown

Type: Dipped Glove
Material: Micro-Foam Nitrile
Outer Liner: 15 Gauge Nylon + Spandex
Cuff: Nylon + Latex Elastic

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov
This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Packaging

	Outer Polybag	Case
GL615	12 Pair	120 Pair
Made in China		

Product markings may vary // Updated as of 11.25

Glove Sizing

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.