PYRAMEX

NITRILE DIPPED

NITRILE | 13-GAUGE | ABRASION | CUT | CONTACT HEAT | PUNCTURE | TEAR

GL616C

Para-Aramid + Steel | Nitrile | Micro-Foam

ANSI/ISEA 105 A6 (5 2) | EN388 4X32D | EN407 X2XXXX | CE | UKCA

ANSI/ISEA 105 – CUT A6 | ABRASION 5 | PUNCTURE 2
EN388 – ABRASION 4 | CUT X | TEAR 3 | PUNCTURE 2 | CUT TDM-100 D
EN407 – CONTACT HEAT 2

Micro-foam nitrile coating on palm and fingers offers an excellent grip on dry or wet surfaces by channeling liquids away // 13G para-aramid liner delivers cut resistance and heat resistance // Contact heat protection up to 482°F/250°C // Knit cuff creates a snug fit to keep out debris



Suggested Applications

General Maintenance // Glass Handling // Manufacturing // Metal Fabrication // Steel Handling// Woodworking

Glove Breakdown

Type: Dipped Glove
Material: Micro-Foam Nitrile
Outer Liner: 13G Para-Aramid + Steel
Cuff: Para-Aramid + Steel + Latex Elastic

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Packaging

	Outer Polybag	Case
GL616C	12 Pair	120 Pair
Made in Pakistan		

Product markings may vary // Updated as of 01.24

Glove Sizing

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.